Scissor Lift License Victoria

Scissor Lift License Victoria - The operation of scissor lifts carries an inherent risk of danger. Whichever kind of powered machinery requires correct handling in order to prevent accidents leading to damage or injury. Businesses must make certain that staff using this equipment have the necessary qualifications.

Unskilled personnel must not be permitted by their companies to utilize scissor lifts. The lift is made to raise materials and people to varied heights. Failure to understand and fully follow safety standard can result in damage to the lift or injuries for users.

Before using the machinery, the scissor-lift operator should carry out a thorough inspection to be able to ensure the machinery is in good working condition. This is the operator's job, even though the unit has already been in service that very same day. The operator's handbook of the machine contains a pre-operation checklist.

Examples of what to look for when doing a pre-operation check include checking tire-inflation pressure, and checking controls in the platform and ground controls to ensure they are functioning. When extending or retracting the boom, look for delayed movement on the fly section that can indicate cables are loose. When operating the controls, make certain that the emergency stop switches work. Operate functions against the equipment's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters should stop the unit automatically before it moves into an unstable position, if they are working right. If they aren't, shut down the lift and ensure that it is fixed before it is utilized for a second time.

Safe operating procedures should be followed always, with the levers being operated with even, controlled pressure. A control lever must never be pushed from one position to the opposite position. The lever must be shifted to neutral, prior to stopping, and then proceeding in the desired direction. When released, control switches and levers should automatically return to the neutral position. Depress the foot switch prior to operating platform controls.